

Lift & Slide Doors

Walls of glass that move with one hand.



MAX PANEL

3.2 × 3.6 m

MAX WEIGHT

600 kg / panel

UW VALUE

from 1.1 W/m²K

WIND LOAD

up to 2,000 Pa

Panels up to 600 kg glide on stainless rollers with a 20 mm sightline option. The flagship for villas, resorts and premium residential.


TECHNICAL DATA

Air permeability	Class 4 EN 12207
Water tightness	E900 (900 Pa) EN 12208
Wind load	C5 (2,000 Pa) EN 12210
Thermal transmittance Uw	from 1.1 W/m²K EN ISO 10077-2
Acoustic insulation	Rw up to 42 dB EN ISO 717-1
Burglar resistance	RC2 EN 1627
Operating force	< 30 N EN 13115
Frame depth	90 / 120 / 160 mm —

GLAZING

- 24–52 mm double or triple IGU
- Low-E, solar control and acoustic laminated
- SGP hurricane interlayer (Florida / cyclonic regions)
- Warm-edge spacer with 90% argon fill


CONFIGURATIONS



2-PANEL · A



4-PANEL · C



3-TRACK · ALL MOVING



CORNER-OPEN

HARDWARE

- HAUTAU HS-Portal or Siegenia lift-and-slide gear
- Stainless 304 / 316 roller carriages
- Multi-point locking with mushroom cams
- Soft-close and motorised drive options

LEAD TIME

25–35 days

MINIMUM ORDER

No minimum for distributors

WARRANTY

10 years system · 15 years coating