ARCVIEW

SPECIFICATION SHEET · 2026

ARC-S90 / S120 SLIM

Lift & Slide Doors

Walls of glass that move with one hand.




MAX PANEL	MAX WEIGHT	UW VALUE	WIND LOAD
3.2 × 3.6 m	**600 kg / panel**	**from 1.1 W/m²K**	**up to 2,000 Pa**

Panels up to 600 kg glide on stainless rollers with a 20 mm sightline option. The flagship for villas, resorts and premium residential.


TECHNICAL DATA

Air permeability	**Class 4** EN 12207
Water tightness	**E900 (900 Pa)** EN 12208
Wind load	**C5 (2,000 Pa)** EN 12210
Thermal transmittance Uw	**from 1.1 W/m²K** EN ISO 10077-2
Acoustic insulation	**Rw up to 42 dB** EN ISO 717-1
Burglar resistance	**RC2** EN 1627
Operating force	**< 30 N** EN 13115
Frame depth	**90 / 120 / 160 mm** –

CONFIGURATIONS



2-PANEL · A



4-PANEL · C



3-TRACK · ALL MOVING



CORNER-OPEN

GLAZING

- 24–52 mm double or triple IGU
- Low-E, solar control and acoustic laminated
- SGP hurricane interlayer (Florida / cyclonic regions)
- Warm-edge spacer with 90% argon fill

HARDWARE

- HAUTAU HS-Portal or Siegenia lift-and-slide gear
- Stainless 304 / 316 roller carriages
- Multi-point locking with mushroom cams
- Soft-close and motorised drive options

LEAD TIME	MINIMUM ORDER	WARRANTY
25–35 days	**No minimum for distributors**	**10 years system · 15 years coating**

export@arcview-systems.com · WhatsApp +86 138 2345 6090 · Foshan Arcview Aluminium Systems Co., Ltd.

Indicative values for standard configurations. Project values are confirmed on shop drawings.